# NSYCVF85M48DPF

ClimaSys forced vent. IP54, 79m3/h, 48V DC, with outlet grille and filter G2





Main	
Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 20869.97 Gal/hr(US) (79 m3/h)
[Us] rated supply voltage	2555.2 V
Input voltage	48 V DC

#### Complementary

Complementary		
Absorbed power	8 W	
Line Rated Current	0.173 A	
Noise level < at	4649 dB	
Bearing type	Ball	
Height	External 6.69 in (170 mm)	
Width	External 5.91 in (150 mm)	
Depth	External 2.44 in (62 mm)	
Cut-out dimensions	125 x 125 mm	
Net Weight	1.06 lb(US) (0.48 kg)	
Material	Outlet grille injected thermoplastic (ASA PC)	
Color	Outlet grille Gray RAL 7032)	
Ambient Air Temperature for Operation	14158 °F (-1070 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Maximum pressure	50 Pa flow rate 0 m³/h	
Connections - Terminals	Cable	
IP degree of protection	IP54	
Device composition	axial motor     protective grille on the front and rear surfaces     filter front of axial motor     outlet grille front     cut-out template     power cord	
Condition of use	Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software	

#### Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151231
Returnability	No
Country of origin	FR

## Packing Units

<b>5</b>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	6.10 in (15.5 cm)
Package 1 Length	7.09 in (18.0 cm)
Package 1 Weight	18.34 oz (520.0 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	20
Package 2 Height	15.75 in (40.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	22.93 lb(US) (10.4 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

### Contractual warranty

Warranty	10 mantha	
Warranty	18 months	
· · · · · · · · · · · · · · · · · · ·		
Wallandy	10 monare	