



ILSCOM® ULT COPPER C CRIMPS



- Manufactured from high strength copper alloy.
- Clearly marked with wire size and die index for easy identification and tooling recommendation.
- Suitable for use in circuits rated at 35 KV or less; proper high voltage spacing and insulation techniques must be used.
- Rated to 90° C.
- UL listed and CSA Certified for grounding and bonding.
- UL 467 Listed for direct burial in earth or concrete.
- Range taking reduces inventory.
- For Copper Conductor only.
- Tested to UL 486A/B,UL File E6207
- Tested to UL 467, UL File E6207
- CSA File LR29601

Item ID	Conductor Range Main	Conductor Range Tap	Length	Die Index Number	Standard Package Quantity	NAED/UPC Number
ULT-1-Z	10 STR-12 SOL	10 STR-12 SOL	0.3660	238	100	0783669930726
ULT-2-Z	8 STR-8 SOL	8 STR-10 SOL	0.4860	162	100	0783669930733
ULT-3-Z	4 STR-6 SOL	8 STR-8 SOL	0.7350	BG OR 5/8	100	0783669930740
ULT-4-Z	4 STR-6 SOL	6 STR-6 SOL	0.7650	BG OR 5/8	100	0783669930757
ULT-5-Z	4 STR-6 SOL	4 STR-4 SOL	0.8300	BG OR 5/8	100	0783669930771
ULT-6-Z	2 STR-2 SOL	4 STR-8 SOL	0.9900	C	100	0783669930795



ILSCOM® ULT COPPER C CRIMPS

Item ID	Conductor Range Main	Conductor Range Tap	Length	Die Index Number	Standard Package Quantity	NAED/UPC Number
ULT-7-Z	2 STR-2 SOL	2 STR-2 SOL	1.0470	C	100	0783669930818
ULT-8-Z	2/0 STR-1/0 SOL	2 STR-8 SOL	1.3500	O	50	0783669930825
ULT-9-Z	2/0 STR-1/0 SOL	2/0 STR-1/0 SOL	1.3500	O	50	0783669930849
ULT-10-Z	4/0 STR-3/0 SOL	2 STR-6 SOL	1.6280	D3	25	0783669930856
ULT-11-Z	4/0 STR-3/0 SOL	2/0 STR-1/0 SOL	1.6280	D3	25	0783669930863
ULT-12-Z	4/0 STR-3/0 STR	4/0 STR-3/0 STR	1.6100	D3	25	0783669930832