GS2SU3

Switch disconnector fuse, TeSys GS, 3P, 600A, fuse type UL, size J



Main	
Range	TeSys
Product name	TeSys GS
Device short name	GS2S
Product or Component Type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[lth] conventional free air thermal current	600 A (at 104 °F (40 °C))
[le] rated operational current	600 A AC-22A 600 A AC-23A
Fuse type	UL
Fuse size	J
Network type	AC DC
Network Frequency	50/60 Hz

Complementary

Type of operating handle	External frontal	
Mounting Support	Plate	
[Uimp] rated impulse withstand voltage	12 kV	
Short-circuit withstand	200 kA	
Connections - terminals	Power circuit lugs-ring terminals 2 0.23 in² (150 mm²) Power circuit bars 0.16 in² (100 mm²)	
Tightening torque	Power circuit 309.78 lbf.in (35 N.m)	

Environment

Standards	CSA C22.2 No 4 UL98	
IP degree of protection	IP20 IEC 60529 with terminal cover)	
Ambient Air Temperature for Operation	-4158 °F (-2070 °C)	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	
Fire resistance	1760 °F (960 °C) body	
Height	11.81 in (300 mm)	
Width	14.33 in (364 mm)	
Depth	9.84 in (250 mm)	
Net Weight	63.93 lb(US) (29 kg)	

Ordering and shipping details

l11
3389119411448
Yes
FR
-

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.60 in (44.7 cm)
Package 1 Width	16.42 in (41.7 cm)
Package 1 Length	20.83 in (52.9 cm)
Package 1 Weight	63.93 lb(US) (29.0 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes

Contractual warranty

Warranty	18 months