



## Main

|                           |                                                                                  |
|---------------------------|----------------------------------------------------------------------------------|
| Range                     | ClimaSys                                                                         |
| Product name              | ClimaSys CV                                                                      |
| Product or Component Type | Fan                                                                              |
| Type of filter            | Standard                                                                         |
| Flow rate                 | Free flow rate with standard filter: 69214.32 Gal/hr(US) (262 m <sup>3</sup> /h) |
| [Us] rated supply voltage | 25...60 V                                                                        |
| Input voltage             | 48 V DC                                                                          |

## Complementary

|                                       |                                                                                                                                                                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Absorbed power                        | 11 W                                                                                                                                                                                                                                                                                    |
| Line Rated Current                    | 0.24 A                                                                                                                                                                                                                                                                                  |
| Noise level < at                      | 55...56 dB                                                                                                                                                                                                                                                                              |
| Bearing type                          | Ball                                                                                                                                                                                                                                                                                    |
| Height                                | External 10.55 in (268 mm)                                                                                                                                                                                                                                                              |
| Width                                 | External 9.76 in (248 mm)                                                                                                                                                                                                                                                               |
| Depth                                 | External 4.07 in (103.4 mm)                                                                                                                                                                                                                                                             |
| Cut-out dimensions                    | 223 x 223 mm                                                                                                                                                                                                                                                                            |
| Net Weight                            | 2.43 lb(US) (1.1 kg)                                                                                                                                                                                                                                                                    |
| Material                              | Outlet grille injected thermoplastic (ASA PC)                                                                                                                                                                                                                                           |
| Color                                 | Outlet grille Gray RAL 7035)                                                                                                                                                                                                                                                            |
| Ambient Air Temperature for Operation | 14...158 °F (-10...70 °C)                                                                                                                                                                                                                                                               |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)                                                                                                                                                                                                                                                              |
| Maximum pressure                      | 158 Pa flow rate 0 m <sup>3</sup> /h                                                                                                                                                                                                                                                    |
| Connections - Terminals               | Cable                                                                                                                                                                                                                                                                                   |
| IP degree of protection               | IP54                                                                                                                                                                                                                                                                                    |
| Device composition                    | 1 axial motor<br>2 protective grille on the front and rear surfaces<br>1 filter front of axial motor<br>1 outlet grille front<br>1 cut-out template<br>1 power cord                                                                                                                     |
| Condition of use                      | Surrounding environment must be relatively clean<br>Filter must be cleaned and replaced regularly<br>Flow rates depends on the work point, see ProClima software<br>Outside temperature must be 5 °C lower than inside temperature<br>Overfrequent filter replacement should be avoided |

## Ordering and shipping details

|                   |                                     |
|-------------------|-------------------------------------|
| Category          | 80036-ENCLOSURE SYSTEMS ACCESSORIES |
| Discount Schedule | ES1                                 |
| GTIN              | 3606480151316                       |
| Returnability     | No                                  |
| Country of origin | FR                                  |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 7.09 in (18 cm)       |
| Package 1 Width              | 9.84 in (25 cm)       |
| Package 1 Length             | 11.02 in (28 cm)      |
| Package 1 Weight             | 3.00 lb(US) (1.36 kg) |
| Unit Type of Package 2       | PAM                   |
| Number of Units in Package 2 | 50                    |
| Package 2 Height             | 39.37 in (100 cm)     |
| Package 2 Width              | 39.37 in (100 cm)     |
| Package 2 Length             | 47.24 in (120 cm)     |
| Package 2 Weight             | 182.98 lb(US) (83 kg) |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                       |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>     |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|