

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 1076.250

Date : Aug 5, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 1076.250 - WM302408NC

: 05.08.2016 build on www.rittal.com/ca-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Packaging unit:	1 pc(s).
EAN:	83111

Product features

Dimensions:	Height: 760 mm (30 ") Width: 600 mm (24 ") Depth: 210 mm (8.3 ")
-------------	--

Material thickness:	Housing: 1.5 mm (0.06 ")
---------------------	--------------------------

Door: 2 mm (0.08 ")
Mounting plate: 2.5 mm (0.1 ")

Mounting plate:	Height: 730 mm (29 ") Width: 549 mm (22 ")
------------------------	---

Weight/pack:	31 kg
---------------------	-------

Approvals

Approvals:	 UL (EN)
-------------------	---

Downloads

Data sheets:	Graphics (US)
---------------------	-------------------------------

Documentation:	 Further information (US)  Info sheet (US)
-----------------------	---

CAD drawings:	Request
----------------------	-------------------------