



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Limit switches XC Standard   |
| Series name                   | Standard format  |
| Product or component type     | Limit switch body  |
| Device short name             | ZCKL   |
| Body type                     | Fixed  |
| Product compatibility         | XCKL   |
| Associated head               | ZCKD109<br>ZCKD02<br>ZCKD10<br>ZCKD21<br>ZCKD17<br>ZCKD23<br>ZCKD239<br>ZCKD59<br>ZCKD029<br>ZCKD219<br>ZCKD06<br>ZCKD15<br>ZCKD81<br>ZCKD41<br>ZCKD08<br>ZCKD16<br>ZCKD91<br>ZCKD05 |
| Body material                 | Metal  |
| Cable entry                   | 1 entry tapped for 1/2" NPT conduit  |
| Number of poles               | 3  |
| Contacts type and composition | 1 NC + 2 NO  |
| Contact operation             | Snap action  |
| Number of steps               | 1 1 position   |
| Contacts material             | Silver plated contacts   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

|  |   |
|--|---|
| Local display                                | Without   |
| Electrical connection                        | Screw-clamp terminals 1 x 0.34...2 x 0.75 mm <sup>2</sup>   |
| Positive opening                             | With  |
| Minimum actuation speed                      | 0.01 m/min  |
| [Ie] rated operational current               | 1.5 A at 240 V, AC-15, B300 conforming to EN/IEC 60947-5-1 appendix A<br>0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1 appendix A  |
| [Ithe] conventional enclosed thermal current | 6 A   |
| [Ui] rated insulation voltage                | 400 V (pollution degree 3) conforming to IEC 60947-1 for contact block<br>300 V conforming to CSA C22.2 No 14 for contact block<br>300 V conforming to UL 508 for contact block   |
| Maximum resistance across terminals          | 0.25 mOhm conforming to IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 6 kV IEC 60664<br>6 kV IEC 60947-1  |
| Short-circuit protection                     | 10 A cartridge fuse gG  |
| Electrical durability                        | 5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width  | 2.52 in (64 mm)   |
| Height                                       | 2.52 in (64 mm)   |
| Depth  | 1.18 in (30 mm)   |
| Net weight                                   | 0.46 lb(US) (0.21 kg)   |
| Terminals description ISO n°1                | (21-22)NC<br>(13-14)NO  |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP66  |
| IK degree of protection               | IK05  |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) standard environment |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                      |
| Environmental characteristic          | Standard environment                            |

## Packing Units

|                              |                  |
|------------------------------|------------------|
| Unit Type of Package 1       | PCE              |
| Number of Units in Package 1 | 1                |
| Package 1 Weight             | 8.15 oz (231 g)  |
| Package 1 Height             | 1.30 in (3.3 cm) |
| Package 1 width              | 3.15 in (8 cm)   |
| Package 1 Length             | 2.56 in (6.5 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---