

XS112BLPAM12

PROX M12 24Vdc PNP NO 3W FLUSH M12 CON

Main

Ampere Rating	50mA
Ampere Rating	50mA
Approvals	UL Listed - CSA Certified - CE Marked
Approvals	UL Listed - CSA Certified - CE Marked
Body Type	Tubular
Body Type	Tubular
Connection Type	M12 Connector
Connection Type	M12 Connector
Enclosure Material	Nickel Plated Brass
Enclosure Material	Nickel Plated Brass
Marketing Trade Name	Osiprox
Marketing Trade Name	Osiprox
Maximum Operating Frequency	2000Hz
Maximum Operating Frequency	2000Hz
Maximum Voltage Rating	36VDC
Maximum Voltage Rating	36VDC
Mounting Type	Flush (M12)
Mounting Type	Flush (M12)
Nominal Sensing Distance	0 to 1.6mm
Nominal Sensing Distance	0 to 1.6mm
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Output	DC 3-Wire (PNP) - 1 N.O.
Output	DC 3-Wire (PNP) - 1 N.O.
Sensor Diameter	12mm
Sensor Diameter	12mm
Supply Voltage	12/24VDC
Supply Voltage	12/24VDC
Type	XS1
Type	XS1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.