



## Main

Range of Product	Modicon M580
Product or Component Type	Communication module
Product compatibility	Ethernet + X-bus rack

## Complementary

Integrated connection type	1 Ethernet RJ45 1 Gbit/s double shielded twisted pair 1 Ethernet 100 Mbit/s
Web server	For configuration
Transmission support medium	Ethernet backplane
Communication service	OPC UA server Modbus TCP messaging SNMP network management NTP time synchronization Embedded router OPC UA client
Cybersecurity	Role-based access control System hardening Secure communication (HTTPS) Achilles certified Syslog protocol support Transport layer security IPSec SNMP logging Certificate based authentication
Port Ethernet	10/100/1000 BASE-TX
Supply	Internal power supply via rack
Protective treatment	Conformal coating
Marking	CE CSA
Module format	Standard
Current consumption	<= 140 mA 24 V DC
Length	3.39 in (86.05 mm)
Width	1.26 in (32 mm)
Height	5.16 in (131 mm)
Net Weight	0.88 lb(US) (0.4 kg)

## Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Relative humidity	5...95 % at 55 °C
IP Degree of Protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive
Product certifications	CE[RETURN]UL[RETURN]CSA[RETURN]RCM[RETURN]EAC[RETURN]Merchant Navy[RETURN]ATEX zone 2/22[RETURN]IECEx zone 2/22
Standards	IEC 61131-2 IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201 IACS E10 IEC 61000-6-5, interface type 1 and type 2 IEC 61850-3, location G IEC 60079-0
Environmental characteristic	Gas resistant class Gx ISA S71.04 Gas resistant class 3C4 IEC 60721-3-3 Dust resistant class 3S4 IEC 60721-3-3 Sand resistant class 3S4 IEC 60721-3-3 Salt resistant level 2 IEC 68252 Mold growth resistant class 3B2 IEC 60721-3-3 Fungal spore resistant class 3B2 IEC 60721-3-3 Hazardous location class I division 2
Local signalling	For processor running (RUN) 1 LED (green) For processor or system fault (ERR) 1 LED (red) For ETH MS (Ethernet port configuration status) 1 LED (green/red) For Eth NS (Ethernet network status) 1 LED (green/red) For status (STS) 1 LED (green/red) For communication data bus 1 LED (yellow)

## Ordering and shipping details


Category	18160-MODICON M340
Discount Schedule	PC34
GTIN	3606489751371
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.70 in (9.4 cm)
Package 1 Width	6.81 in (17.3 cm)
Package 1 Length	8.54 in (21.7 cm)
Package 1 Weight	9.52 oz (270.0 g)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Dimensions

