

NSYMP208

Plain mounting plate, PanelSeT SFN, Spacial SF, Spacial SM, for electrical enclosure H2000 W800mm, galvanized steel



Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 78.74 in (2000 mm) W: 31.50 in (800 mm)
Mounting plate description	Plain
Range compatibility	Spacial Spacial SF Spacial Spacial SM Spacial Spacial SFX Spacial Spacial SMX
Device composition	1 mounting plate 2 sliding shoes
Quantity per Set	Set of 1
Material	Galvanised steel

Complementary

Fixing mode	By fixing brackets
Maximum load	300 kg/m ²
Permanent permissible load	1102.31 Lb(US) (500 kg) intermediate position 1322.77 lb(US) (600 kg) back of the enclosure
Height	Fixing centers 72.83 in (1850 mm) Nominal 78.74 in (2000 mm) Real 74.69 in (1897 mm)
Width	Nominal 31.50 in (800 mm) Fixing centers 25.59 in (650 mm) Real 27.40 in (696 mm)
Depth	1.06 in (27 mm)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606485126906
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.38 in (3.5 cm)
Package 1 Width	27.56 in (70.0 cm)
Package 1 Length	75.39 in (191.5 cm)
Package 1 Weight	68.34 lb(US) (31.0 kg)
Unit Type of Package 2	P2M
Number of Units in Package 2	20

Package 2 Height	31.50 in (80.0 cm)
Package 2 Width	78.74 in (200.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	1413.16 lb(US) (641.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------