



L1L730D - L1L Series 7,000 Lumen Output 5000K CCT, 120-277 Universal Voltage With Diffuse Glass Optic

By Killark
Catalog # [L1L730D](#)



L1L Series 7,000 Lumen Output 5000K CCT, 120-277 Universal Voltage With Diffuse Glass Optic

Features

-
-
-
-
-
-

General

Catalog Number	L1L730D
Color Temperature	5000 K
EU RoHS Indicator	Contact Manufacturer
Finish Type	Natural
Lumen Range	5,001-10,000 lm
Lumens	5598
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Optic Type	Diffused Glass Lens
Series	L1L
UPC	783936174754

Dimensions

Hub Size	3/4"
----------	------

Electrical Ratings

Lumens Per Watt	120.4
Voltage Rating	120-277 VAC
Wattage	46.5 W

Certifications And Compliance

Hazardous Rating(s)	<ul style="list-style-type: none"> • Class I, Divisions 1 & 2, Groups B, C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
IP Rating	IP66

Product Assets

- [3D Models - L1L Series 3D Model](#)
- [Catalogs - Killark Catalog](#)
- [Certifications - L1L ABS Product Certificate](#)
- [Certifications - L1L Series IECEx Certification](#)
- [Certifications - L1L Series ATEX Certification](#)
- [Certifications - L1L Series Attestation of Conformity](#)
- [Certifications - L1L Series LED Luminaires CSA Cert](#)
- [Installation Manuals - L1L Series IOM K1498](#)
- [Photometry - L1L730D IES File](#)
- [Specifications - L1L730D Specification Sheet English](#)
- [Specifications - L1L730D Specification Sheet French](#)
- [Specifications - L1L Series Specification Sheet](#)
- [Video - L1L Overview](#)
- [Video - L1L Overview](#)