NSYSFX20840

SFX 304L stainless suitable enclosure, H2000xW800xD400mm, Scotch Brite® finish.





Main	
Range	Spacial
Product name	Spacial SFX
Enclosure type	Multi-purpose
Category	Suitable enclosure
Nominal height	78.74 in (2000 mm)
Nominal width	31.50 in (800 mm)
Nominal depth	15.75 in (400 mm)
Product installation	Floor-standing
Device composition	1 structure 1 locking system with handle door 4 mounting plate bracket 1 cable gland plate 1 door with reinforcement frame

Co	mn	l۵r	nar	ıtaı	rv,
\sim 0	ulb	ıcı	1161	ıιa	ΙV

Body type	Rear panel integrated
	Single piece structure folded and welded
Door type	Solid
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 points lock, handle with 5 mm double-bar insert
Mounting plate description	Without mounting plate
Type of gland plate	Plain
Accessibility for operation	Front
	Side
Removable parts	Door by hinges
	Mounting plate bracket by screws
	Cable gland plate by clips
Material	Structure and door stainless steel 304L
	Handle zamak
	Hinge stainless steel
Surface finish	Enclosure Scotch-Brite® brushed
	Handle painted
Net Weight	198.42 lb(US) (90 kg)

Environment

LITTOTITICITE		
Standards	IEC 62208 NEMA 4X	
Product Certifications	UL	
IP degree of protection	IP66 IEC 60529	
IK degree of protection	IK10 IEC 62262	
Environmental characteristic	Corrosive Specific hygiene	

Ordering and shipping details

ES1	
3606480155680	
No	
BG	
	3606480155680 No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.08 in (51.0 cm)
Package 1 Width	33.46 in (85.0 cm)
Package 1 Length	84.25 in (214.0 cm)
Package 1 Weight	200.62 lb(US) (91.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months