

LLA36400CU31X

Circuit breaker, PowerPact L, I-Line, Micrologic 3.3, 400A, 100% rated, 3 pole, 50 kA, 600 VAC, phase ABC



Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Electronic, standard, Micrologic 3.3, LI
Interrupt Code	L

Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC
Voltage Rating	600 V AC
Continuous current rating	100 %
Protection technology	Current limiter
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Terminal Type	AL600LS52K3
Wire Size	AWG 2/0...500 kcmil (aluminium/copper) for 2 cable(s)
Tightening torque	442.54 lbf.in (50 N.m) 0.11...0.37 in ² (70...240 mm ²) AWG 2/0...500 kcmil)
I-Line Phase Connection	ABC
Height	14.7 in (373.38 mm)
Width	5.94 in (150.88 mm)
Depth	6.61 in (167.89 mm)

Environment

Product certifications	CSA 22-2 CCC IEC CE UL 489 NMX NEMA
------------------------	---

Packing Units

Package 1 Weight	17.00 lb(US) (7.711 kg)
------------------	-------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------