

4U Vertical Wall Mount

Description

The 4U Vertical Wall Mount Rack is designed to accommodate all standard 19" telecommunications equipment. Intended for use in the MPOE (Main Point of Entry) or a tight closet where space is limited, the 4U Vertical Wall Mount offers great space savings and can often eliminate the need for an 8U, 12U, or 20U swinging rack or wall mount.

Features and Benefits

14 Gauge (0.0747") Cold Rolled Steel
Cable management bridges included
Fully compatible with all standard 19 inch equipment

Rack mounting hole compliant with CEA-310-E standard E (10-32)
Wall mounting keyholes for easy installation

Applications

Entrance facility
Telecommunications room
Equipment room

Consolidation point
Central office
Cellular tower base station

Certification and Compliance

CEA-310-E
TIA-569
UL 94
RoHS

Cabinets, Racks, Panels, and Associated Equipment
Commercial Building Standard for Telecommunications Pathways and Spaces.
Tests for Flammability of Plastic Material for Parts in Devices and Appliances
Directive on Restriction of Hazardous Substances



Part Number	Description	Packaging
WW-001812	Wall-Mounted 4U Rack	1 unit per box
WW-001819	Wall-Mounted 4U Rack Cover with Window	Inclusion
WW-001818	Wall-Mounted 4U Rack with Cover (WW001812 + WW001819)	8X Wood screws for wall mounting. 3x Blank 1U Strips (only for WW-001818 & WW-001819)

Physical Characteristics

Parameter	Value
Material	WW001812 : Gauge 14 WW001819 : Gauge 16 & 18
Panel finish	Black Sandex
Overall dimensions	WW001812 : 500.9 mm (19.72 in) x 190.5mm (7.50 in) x 190.5 mm (7.5 in) WW001818 : 564 mm (22.2 in) x 332 mm (13.1 in) x 206 mm (8.12 in)

Mechanical Characteristics

Parameter	Value
Installation temperature	-25° C (-13° F) ~ 40° C (104° F)
Storage temperature	-25° C (-13° F) ~ 55° C (131° F)
Relative humidity	≤ 85% (30° C)

Related Products

- Drop Cassette
- LGX Strips (Copper or Fiber)
- Single LGX Wall Mount
- Triple LGX Wall Mount

