



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 11623.78 Gal/hr(US) (44 m ³ /h)
[Us] rated supply voltage	36...56 V
Input voltage	48 V DC

Complementary

Absorbed power	3.6 W
Line Rated Current	0.07 A
Noise level < at	40...41 dB
Bearing type	Ball
Height	External 5.39 in (137 mm)
Width	External 4.61 in (117 mm)
Depth	External 1.93 in (49 mm)
Cut-out dimensions	92 x 92 mm
Net Weight	0.51 lb(US) (0.23 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
Color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14...158 °F (-10...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Maximum pressure	29 Pa flow rate 0 m ³ /h
Connections - Terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template
Condition of use	Outside temperature must be 5 °C lower than inside temperature Surrounding environment must be relatively clean Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software Filter must be cleaned and replaced regularly

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151194
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 in (15 cm)
Package 1 Width	5.91 in (15 cm)
Package 1 Length	3.94 in (10 cm)
Package 1 Weight	9.35 oz (265 g)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------