

Eaton CRL530C

Catalog Number: CRL530C

Eaton corrosion resistant locking connector , #14-10 AWG, 30A, Industrial, 125V, Back wiring, Yellow, Safety grip, Corrosion resistant, L5-30, Two-pole, Three-wire, Santoprene thermoplastic elastomeric, 0.38 to 1 in



General specifications

Product Name	Catalog Number
Eaton Arrow Hart corrosion resistant locking connector	CRL530C
	UPC
	040893679525
Product Length/Depth	Product Height
2.12 in	3.44 in
Product Width	Product Weight
2.12 in	0.4 lb
Compliances	Certifications
RoHS Compliant	NOM
Federal Specifications Classification W-C375	CSA certified
	UL Listed
	cULus Listed

Electrical Ratings

Amperage Rating

30A

NEMA configuration

L5-30

Operating temperature

-20 to 75 °C (-4 to 167 °F)

Torque rating

14-16 lbf-inch

Voltage rating

125 V

Wiring method

Back

Environmental Specifications

Environmental conditions

Corrosion resistant

Environmental resistance

Corrosion resistant

Material Specifications

Color

Yellow

Contact material

Nickel plated brass

Face/body material

Nylon

Material

Nylon

Product Specifications

Allowable wire size

#14-8 AWG

Application

Industrial

Cord diameter

0.38-1 in (9.5 mm-25.4 mm)

Design type

Industrial grip

Device grade

Extra heavy-duty industrial specification grade

Number Of Poles

Two-pole

Type

Locking connector

Resources

Brochures

[Complex environment devices brochure](#)

Specifications and datasheets

[Eaton Specification Sheet - CRL530C](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)