SSP02EMA24DF

Surge protection device, Surgelogic, 240kA, 208Y/120 VAC, 3 phase, 4 wire, NEMA 1, disconnect switch, enhanced filter



Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	EMA

Complementary

Complementary		
Voltage Rating	208Y/120 V AC	
MCOV	150 V	
SCCR	200 kA	
Surge Current	240 kA	
Nominal Discharge Current	20 kA	
Rated Current	150 A	
Number of Phases	3 phase	
Max Number of Poles	3	
Wiring Configuration	4-wire	
Connection	Lugs AWG 10AWG 3/0 copper 35.40 lbf.in (4 N.m)	
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault	
Provided Equipment	Alarm enable/disable switch Switch-disconnector Surge counter Sine wave tracking module Dry contacts	
Cable length	19.02 in (483 mm)	
Device Mounting	Surface	
Height	19.49 in (495 mm)	
Width	9.88 in (251 mm)	
Depth	5.31 in (135 mm)	

Environment

Ambient Operating	149 °F (65 °C)	
Enclosure Rating	NEMA 1	
Enclosure Material	Gray painted sheet steel	
Standards	CSA C22.2 No 8 UL 1449:ed. 4	
	UL 1283:ed. 5	

Ordering and shipping details

Category	08464-SURGE PROTECTION EMA
Discount Schedule	DE1B
GTIN	3606486148549
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.49 in (49.5 cm)
Package 1 Width	9.88 in (25.1 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	20.50 lb(US) (9.299 kg)

Offer Sustainability

REACh Declaration
Compliant with Exemptions
China RoHS Declaration
₫ Ves