



Main

Range of Product	PowerLogic T300
Product or Component Type	Voltage adaptor

Complementary

Rated voltage	11...36 kV
Input voltage	1...30 V AC L-L)
Input voltage limits	< 30 V
Network Frequency	50/60 Hz
Electrical connection	Output: connector RJ45 Input: connector micro-fit

Environment

Fixing mode	By clamp plastic)
Operating position	Vertical Horizontal
Standards	IEC 62271-206
Product Certifications	CE
IP degree of protection	IP30 conforming to IEC 60529
IK degree of protection	IK07 IEC 62262
Ambient Air Temperature for Operation	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Fire resistance	1562 °F (850 °C) IEC 60695-2-11
Environmental characteristic	Salt mist 200 h IEC 60068-2-11
Relative humidity	95 % IEC 60068-2-30
Operating altitude	<= 6561.68 ft (2000 m)
Height	1.97 in (50 mm)
Width	1.97 in (50 mm)
Length	3.94 in (100 mm)
Net Weight	0.08 lb(US) (0.038 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.85 in (4.7 cm)
Package 1 Width	1.73 in (4.4 cm)
Package 1 Length	3.66 in (9.3 cm)
Package 1 Weight	1.69 oz (48.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	72

Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	8.58 lb(US) (3.891 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.