9001SKS42FRH37

Selector switch, Harmony 9001SK, plastic, long handle, red, 30mm, 3 positions, stay put, 1 NC + 1 NO





Main

Range of Product	Harmony 9001SK	
Product or Component Type	Selector switch	
Device short name	9001SK	

Complementary

- Comprehensive		
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Operator position information	3 positions	
Contacts type and composition	1 NC + 1 NO	
Device presentation	Complete product	
Cap/operator or lens colour	Red	
Operator profile	Long handle	
Type of operator	Stay put	
Size	30 mm	
Cam profile	2	

Environment

Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
Product Certifications	UL listed file E42259 CCN NKCR[RETURN]CSA LR24590 class 3211 03[RETURN]CE

Ordering and shipping details

Category	21429-9001 SK,SKY	
Discount Schedule	CS1	
GTIN	785901328100	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 Width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	
Package 1 Weight	3.20 oz (90.719 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	[™] REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty	18 months