

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings L5 and L5R.

CONSTRUCTION

Antique bronze, oil-rubbed bronze, brushed nickel and white finishes are one-piece aluminum open reflectors.

INSTALLATION

Socket to trim interface.

Trim retention is achieved by utilizing two side-mounted torsion springs on the trim and two receiving brackets in the can, ensuring a consistently tight fit with the ceiling.

LISTINGS

UL Listed to U.S. and Canadian safety standards.

Damp location listed.


Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

5" Finishing Trim

5B2


BAFFLE DEEP
Narrow Flange



Specifications

Height: 5-3/8" (13.7)
Lamp opening: 5-1/8" (13.0)
Diameter: 6-3/8" (16.2)

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

Example: 5B2 TOR

Series	Finish	Mounting method	Packaging
5B2	(blank) Black baffle, white flange TRMW Black baffle, matte white flange W White baffle MW Matte white BN Brushed nickel baffle BZA Antique bronze baffle ¹ ORB Oil-rubbed bronze baffle	TOR Torsion springs	R12 Resale pack of twelve R6 Resale pack of six U Unit

Housing Compatibility: Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	50 R20 (white only)	L5, L5R
		65 BR30 (white only)	L5, L5R
		75 PAR30 (white only)	L5, L5R
		50 PAR30	L5, L54
		60 PAR38	LC5, L5R

Notes

1 R12 only available in BZA (antique bronze) finish.

5B2 5" Baffle Deep Full Reflector Trim

For BR and PAR reflector lamps, see lamp manufacturer's published raw lamp data for photometrics.