# 8536SCO3V01S

NEMA motor starter, Type S, nonreversing, Size 1, 27A, 10HP at 460VAC, 5kA SCCR, 3 phase, 3 pole, melting alloy, 24VAC coil, open



### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

Complementary	
NEMA Size	1
Rated Current	27 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phase
Type of Overload	Melting alloy 3
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
Coil Voltage	24 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Screw clamp terminals
Height	6.81 in (172.96 mm)
Width	3.50 in (88.90 mm)
Depth	4.22 in (107.19 mm)
	<del></del>

### **Environment**

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA

## Ordering and shipping details

21192-8502,36 SC,SD(NOT S*R,T,W)
CP1
785901439813
Yes
MX

Pac	kin	a L	Inits

PCE
1
4.60 in (11.684 cm)
5.90 in (14.986 cm)
7.90 in (20.066 cm)
4.05 lb(US) (1.837 kg)

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	☑ China RoHS Declaration	
PVC free	Yes	

# Contractual warranty

Contractada Warranty	
Warranty	18 months