760236110 | DM12-24LC-LS-ULL



G2 ULL Multimode OM4 MPO-12 Distribution Module, 24LC to 2X12f MPOs unpinned, internal shutters

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

 Portfolio
 CommScope®

 Product Type
 Fiber module

 Product Brand
 SYSTIMAX ULL

Product Series G2

General Specifications

Color, frontAquaColor, rearGrayInterface, frontLC

Interface Feature, front Standard

Interface, rear MPO Unpinned

Interface Feature, rear Key up/up

Polarity Method B Enhanced (ULL)

Shuttered Yes
Total Fibers, quantity 24

Dimensions

 Height
 26.42 mm | 1.04 in

 Width
 96.52 mm | 3.8 in

 Depth
 117.35 mm | 4.62 in

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4, LazrSPEED® 550

Insertion Loss, maximum 0.35 dB



760236110 | DM12-24LC-LS-ULL

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL

Packaging and Weights

Packaging quantity

Weight, net 0.113 kg | 0.249 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



