

CHOM60120M150GC

Loadcentre, Homeline, 1 phase, 42 spaces, 84 circuits, 150A main breaker, Type 1, gnd bar, combo cover



Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	150 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	22 kA

Complementary

Electrical Connection	Lugs
AWG gauge	AWG 4...250 kcmil aluminium/copper
Load center type	Main breaker
Number of spaces	60
Number of circuits	120
Number of tandem circuit breakers	60
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	White
Box number	24

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	39997-CANADIAN PRODUCTS
Discount Schedule	NET
GTIN	3606486138489
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.00 in (15.24 cm)
Package 1 Width	52.00 in (132.08 cm)
Package 1 Length	17.00 in (43.18 cm)
Package 1 Weight	47.00 lb(US) (21.319 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations