



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Protection accessories
Accessory / separate part type	Protective screen
Product compatibility	XUSL.E...31
Accessory / separate part destination	Safety light curtain type 2 Safety light curtain type 4
Height	13.58 in (345 mm)
Quantity per set	Set of 4

Complementary

Material	Polycarbonate
Sensing distance reduction coefficient	0.97 Sn
Net weight	0.31 lb(US) (0.14 kg)

Environment

Resistance to chemical agents	Resistant aqueous solutions Resistant to inorganic diluted acids Resistant detergents and cleaners Resistant alkalis
Ambient air temperature for operation	14...131 °F (-10...55 °C) 14...131 °F (-10...55 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C) -13...158 °F (-25...70 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	28.22 oz (800 g)
Package 1 Height	5.51 in (14 cm)


Package 1 width	7.87 in (20 cm)
Package 1 Length	18.11 in (46 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Mounting and Clearance

Various Stages in the Protective Screen Assembly



(1) Depending on the length