CHU364RB

Electrical Connection

Duty Rating

200A 3P Type3R 600VAC/DC Heavy Duty Non-Fusible Safety Switch





Main Product Single Throw Safety Switch Disconnect Type Non-fusible disconnect Number of Poles 3

Lugs

Heavy duty

Complementary

Complementary	
Line Rated Current	200 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Wire Size	AWG 6250 kcmil copper or aluminium
Maximum Horse Power Rating	15 Hp 240 V AC 5060 Hz 1 phase NEC 240.6 60 Hp 240 V AC 5060 Hz 3 phase NEC 430.52 50 Hp 480 V AC 5060 Hz 1 phase NEC 240.6 125 Hp 480 V AC 5060 Hz 3 phase NEC 430.52 50 Hp 600 V AC 5060 Hz 1 phase NEC 240.6 150 Hp 600 V AC 5060 Hz 3 phase NEC 430.52 50 Hp 250 V DC 50 hp at 600 V DC
Height	29.25 in (742.95 mm)
Maximum Width	18.63 in (473.20 mm)
Depth	8.5 in (215.90 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.30127 mm²) AWG 6250 kcmil)

Environment

Certifications	CUL
Enclosure Rating	NEMA 3R galvannealed steel

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG	
Discount Schedule	DE1	
GTIN	00785901994671	
Nbr. of units in pkg.	1	
Package weight(Lbs)	53 lb(US) (24.04 kg)	
Returnability	Yes	
Country of origin	US	

Packing Units

Package 1 Height	8.40 in (21.336 cm)
Package 1 width	19.50 in (49.530 cm)
Package 1 Length	30.20 in (76.708 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes