# NSYTBP241912H

PC box IP66 IK08 RAL7035 Int.H225W175D120 Ext.H241W194D127 opaque PC cover H40





#### Main

Range	Thalassa	
Product name	Thalassa TBP	
Device Application	Multi-purpose	
Category	Industrial box	
Height	9.49 in (241 mm)	
Width	7.64 in (194 mm)	
Depth	5.00 in (127 mm)	
Internal height	8.86 in (225 mm)	
Internal width	6.89 in (175 mm)	
Internal depth	4.72 in (120 mm)	
Enclosure mounting	Wall mounted	
Device composition	1 body	
	1 cover	
	4 cover screw	
Body type	One piece moulded	
Type of front cover	High plain cover	
Cover fixing	Plastic screws	
Lock type	Captive screw flat outside sealed area	
Removable parts	Cover by captive screws	

#### Complementary

Material	polycarbonate	
Color	Gray RAL 7035)	
Standards	UL 508 A IEC 62208	
Product Certifications	TÜV[RETURN]UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor (with canopy or shelter and anticondensation valve)	
Net Weight	1.72 lb(US) (0.78 kg)	

#### Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

#### Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480165719	
Yes	
HU	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.51 in (14 cm)
Package 1 Width	7.87 in (20 cm)
Package 1 Length	10.04 in (25.5 cm)
Package 1 Weight	30.97 oz (878 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	15.75 in (40 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	16.14 lb(US) (7.32 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Height	47.24 in (120 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	53.15 in (135 cm)
Package 3 Weight	220.46 lb(US) (100 kg)

## Offer Sustainability

☑ REACh Declaration	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration	
Yes	
Yes	
<sup>™</sup> China RoHS Declaration	
₽	
Product Environmental Profile	
End Of Life Information	

### Contractual warranty

Warranty	18 m	onths
vvarianty	10 111	ontrio