

The TCP Wrap Light offers superior light output in a maintenance-free fixture. With a durable metal frame, and a glare free, impact resistant frosted lens, you can install these fixtures and relax. Built to industry standard measurements, installation is quick and easy, and provides for easy upgrading.

Reasons to choose the LED Wrap Light from TCP

- Energy efficient LED luminaire
- Smooth, uniform dimming (0-10V)
- Instant on, no warm up time for full light
- Long life: 50,000 hours
- Replaces traditional linear fluorescent systems
- Heavy duty steel housing

Ideal Applications

- Warehouses & Distribution Centers
- Commercial Facilities
- Aisles (Open & Stock)
- Restrooms
- Corridors

- Stairwells
- Hallways











Applications

The TCP Wrap Light offers superior light output in a maintenance free fixture. With a durable metal frame, and a glare free, impact resistant lens, you can install these fixtures and relax. Built to industry standard measurements, installation is quick and easy, and provides for easy upgrading.

Construction

- Housing: durable steel construction
- Finish: powder coated, post-painted white
- Large wiring compartment and knock-outs to accommodate lighting controls
- Easy surface mount, suspended or pendant installation


Electrical


- Universal 120-277V
- cULus damp location rated
- 0-10V dimming driver (standard)
- Easy-to-access wiring compartment
- System rated for long 50,000 hour life

Optics

- High impact, acrylic lens comes standard to protect the LEDs and minimize glare
- Delivers bright, white light and excellent uniformity







ITEM #	DESCRIPTION	DLC	LUMENS	WATTAGE	LPW	VOLTAGE	POWER FACTOR	ССТ	CRI	LIFE	L (INCHES)	W (INCHES)	H (INCHES)
LWR2300135	LED WRAP LIGHT - 3500K	*	3300	23	150	120-277V	>0.9	3500K	80	50,000	47.7	<i>7</i> .1	2.8
LWR2300140	LED WRAP LIGHT - 4000K	*	3400	23	150	120V-277V	>0.9	4000K	80	50,000	47.7	<i>7</i> .1	2.8
LWR2300150	LED WRAP LIGHT - 5000K	*	3500	23	150	120V-277V	>0.9	5000K	80	50,000	47.7	<i>7</i> .1	2.8
LWR3500135	LED WRAP LIGHT - 3500K	*	5100	35	150	120V-277V	>0.9	3500K	80	50,000	47.7	<i>7</i> .1	2.8
LWR3500140	LED WRAP LIGHT - 4000K	*	5200	35	150	120V-277V	>0.9	4000K	80	50,000	47.7	<i>7</i> .1	2.8
LWR3500150	LED WRAP LIGHT - 5000K	*	5250	35	150	120V-277V	>0.9	5000K	80	50,000	47.7	<i>7</i> .1	2.8
LWR6300135	LED WRAP LIGHT - 3500K	*	7700	63	125	120V-277V	>0.9	3500K	80	50,000	47.7	<i>7</i> .1	2.8
LWR6300140	LED WRAP LIGHT - 4000K	*	7900	63	125	120V-277V	>0.9	4000K	80	50,000	47.7	7.1	2.8
LWR6300150	LED WRAP LIGHT - 5000K	*	8050	63	125	120V-277V	>0.9	5000K	80	50,000	47.7	<i>7</i> .1	2.8

For the most up-to-date specs and warranty information, please visit www.tcpi.com









TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	TCD.
Rep:	TCP we know light.™