



L1L730C - L1L 7,000 Lumen Output 5000K CCT, 120-277 Universal Voltage

By Killark
Catalog # [L1L730C](#)



L1L Series 7,000 Lumen Output 5000K CCT, 120-277 Universal Voltage with Clear Glass Optic

Features

Optional supplementary surge protection available 20KA/10KV (120-277 VAC), 10KA/10KV (347-480 VAC)

General

Catalog Number	L1L730C
Color Temperature	5000 K
EU RoHS Indicator	Contact Manufacturer
Finish Type	Natural
Lumen Range	5,001-10,000 lm
Lumens	7147
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Optic Type	Glass Lens
Series	L1L
UPC	783936174747

Dimensions

Hub Size	3/4"
----------	------

Electrical Ratings

Lumens Per Watt	153.7
Voltage Rating	120-277 VAC

Wattage	46.5 W
---------	--------

Certifications And Compliance

Hazardous Rating(s)	<ul style="list-style-type: none">Class I, Divisions 1 & 2, Groups B, C, DClass II, Divisions 1 & 2, Groups E, F, GClass III, Divisions 1 & 2
IP Rating	IP66

Product Assets

- [3D Models - L1L Series 3D Model](#)
- [Certifications - L1L ABS Product Certificate](#)
- [Certifications - L1L Series IECEx Certification](#)
- [Certifications - L1L Series ATEX Certification](#)
- [Certifications - L1L Series Attestation of Conformity](#)
- [Certifications - L1L Series LED Luminaires CSA Cert](#)
- [Installation Manuals - L1L Series IOM K1498](#)
- [Photometry - L1L730C IES File](#)
- [Specifications - L1L730C Specification Sheet English](#)
- [Specifications - L1L730C Specification Sheet French](#)
- [Specifications - L1L Series Specification Sheet](#)
- [Video - L1L Overview](#)
- [Video - L1L Overview](#)