

Tel.: 514 695-8228 1 855 739-8228

Fax: 514 695-9009 1 855 812-9009



APX-LED-810

8" HIGH PERFORMANCE APEX SERIES - 30W

Product codes

APX810-2530-3K-WH: WHITE-WHITE 3K APX810-2530-4K-WH: WHITE-WHITE 4K APX810-2530-3K-WCH: WHITE-CHROME 3K APX810-2530-4K-WCH: WHITE-CHROME 4K APX810-2530-5K-WH: WHITE-WHITE 5K APX810-2530-5K-WCH: WHITE-CHROME 5K

This high performance LED recessed downlight comes with a pressure-fit spring clips for an easy installation. Integrated LED technology offers low-energy, long lasting performance with outstanding light outputs up to 2500 lumens.

The polycarbonate 60 degree reflector is designed for maximum reflection efficiency. The deep regressed diffuser is designed to eliminate the glare from the high powered LED. It is available with a White or Chrome reflector.

The body is constructed of die cast aluminum in 3", 4", 6" & 8" trim sizes with a junction box manufactured in aluminum extrusion. Designed to replace existing CFL/PL, fluorescent or incandescent fixtures. Well adapted for any new, remodel or old commercial applications. For easy and quick installation, the unit comes with pressure-fit spring clips, quick connect wire connectors. It is IC and damp rated.

It features a 0-10V dimmable driver (120-277V). An optional 120V and/or 347V dimmable driver are available

8.66°		# 8.66°
))h	100mm
	_	8.0° 203rem →
		0 3.5'

Cutting note	7.75 (196.9 11111)
Beam Angle	60�
Color Temperature	3K / 4K / 5K
Mounting Plate	MPHB-800
CRI	>80
Voltage	120-277V
Dimmable	0-10V DIM
Volt - Special Order	120V / 347V

7.75" (106.0 mm)

120V / 347V - DIM

4E 000b--

Donni; ½es techniques

Cutting holo

Dimmable

D. . IL | 1 :4 ~