

**S..Al / S..SS****EEMAC / NEMA 4-4x-12 / IP-65**  
**Hinged Lift-Off Cover Enclosures****Hinged Lift-Off Aluminium Enclosures****TECHNICAL READOUT**

Catalog No.	Dimensions			Panel		Weight lbs
	A	B	C	E	F	
S040403AL	4	4	3	no panel		1
S060403AL	6	4	3	4.875	x 2.875	1.5
S060604AL	6	6	4	4.875	x 4.875	2.5
S080604AL	8	6	4	6.875	x 4.875	3.5
S100804AL	10	8	4	8.875	x 6.875	4.5
S121005AL	12	10	5	10.875	x 8.875	7
S141206AL	14	12	6	12.875	x 10.875	10
S161406AL	16	14	6	14.875	x 12.875	13
S141208AL	14	12	8	12.875	x 10.875	12
S161410AL	16	14	10	14.875	x 12.875	15

**Application:**

Type 4-4x-12 / IP-65 aluminium enclosure designed for INDOOR/OUTDOOR housing of electrical, pneumatic or hydraulic instruments where corrosion is a determining factor.

**Construction:**

- Quality utility grade aluminium
- Continuously welded and ground smooth seams
- 1/4 turn latches
- Galvanized steel panel natural finish (unpainted)
- Grounding screw on mounting panel
- Grounding stud welded on inner cover surface
- ANSI/ASA61 grey polyester - epoxy textured powder coating inside out

**Also Available:**

- Aluminium, SS, galvanized steel
- Cutouts, hubs
- Special finishes & sizes

**Standards:**

- CSA certified 150359
- UL listed E109310
- CE

**Hinged Lift-Off Stainless Steel Enclosures****TECHNICAL READOUT**

Catalog No.	Dimensions			Panel		Weight lbs
	A	B	C	E	F	
S060404SS	6	4	4	4.875	x 2.875	4
S060604SS	6	6	4	4.875	x 4.875	5
S080604SS	8	6	4	6.875	x 4.875	6
S100804SS	10	8	4	8.875	x 6.875	10
S121005SS	12	10	5	10.875	x 8.875	15
S121206SS	12	12	6	10.875	x 10.875	17
S141206SS	14	12	6	12.875	x 10.875	21
S161406SS	16	14	6	14.875	x 12.875	26
S141208SS	14	12	8	12.875	x 10.875	22
S161410SS	16	14	10	14.875	x 12.875	28

**Application:**

Type 4-4x-12 / IP-65 stainless steel enclosure designed for INDOOR/OUTDOOR housing of electrical, pneumatic or hydraulic instruments where corrosion is a determining factor.

**Construction:**

- 16 gauge 304-4 stainless steel
- 14 gauge galvanized steel panel natural finish (unpainted)
- Continuously welded and ground smooth seams
- 1/4 turn latches
- Grounding screw on mounting panel
- Grounding stud welded on inner cover surface

**Also Available:**

- Cutouts, hubs
- Special finishes

**Standards:**

- CSA certified 150359
- UL listed E109310
- CE

**BEL Products Inc.**

Technical specifications subject to change without notice. 06/2009