NSYSFX201260

SFX 304L stainless suitable enclosure, H2000xW1200xD600mm, Scotch Brite® finish.





Main	
Range	Spacial
Product name	Spacial SFX
Enclosure type	Multi-purpose
Category	Suitable enclosure
Nominal height	78.74 in (2000 mm)
Nominal width	47.24 in (1200 mm)
Nominal depth	23.62 in (600 mm)
Product installation	Floor-standing
Device composition	structure door with reinforcement frame locking system with handle door mounting plate bracket cable gland plate

0-				4	
Cor	ומת	ıen	าen	ıtar\	/

Body type	Single piece structure folded and welded Rear panel integrated	
Door type	Solid	
Number of doors	Front face 2	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, handle with 5 mm double-bar insert	
Mounting plate description	Without mounting plate	
Type of gland plate	Plain	
Accessibility for operation	Front	
	Side	
Removable parts	Door by hinges	
	Mounting plate bracket by screws	
	Cable gland plate by clips	
Material	Structure and door stainless steel 304L	
	Handle zamak	
	Hinge stainless steel	
Surface finish	Enclosure Scotch-Brite® brushed	
	Handle painted	
Net Weight	250.22 lb(US) (113.5 kg)	

Environment

Standards	IEC 62208	
IP degree of protection	IP55 IEC 60529	
IK degree of protection	IK10 IEC 62262	
Environmental characteristic	Corrosive Specific hygiene	

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606480155666
Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.56 in (70.0 cm)
Package 1 Width	49.21 in (125.0 cm)
Package 1 Length	83.46 in (212.0 cm)
Package 1 Weight	304.24 lb(US) (138.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months