



Main

Range	Mureva
Range of Product	Mureva lights
Product or Component Type	Floodlight
Device Application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of Installation	Outdoor
Total system power	100 W
Light source	LED
[Ue] rated operational voltage	120 V AC
Power factor	0.9
Colour rendering index	R _a =80
Luminous flux	10500 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour tint	black
Beam angle	110 °
Shape	Rectangular
Height	11.35 in (288.4 mm)
Width	8.52 in (216.4 mm)
Depth	1.55 in (39.3 mm)
Net Weight	4.30 lb(US) (1.95 kg)

Environment

Environmental characteristic	Weatherproof
IP Degree of Protection	IP65
IK degree of protection	IK05
Ambient Air Temperature for Operation	-22...113 °F (-30...45 °C)

Ordering and shipping details

Category	18160-MODICON M340
Discount Schedule	PC34
GTIN	3606489903367
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.28 in (5.8 cm)
Package 1 Width	9.25 in (23.5 cm)
Package 1 Length	11.65 in (29.6 cm)
Package 1 Weight	4.52 lb(US) (2.052 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	28.69 lb(US) (13.015 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	29.53 in (75 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	47.24 in (120 cm)
Package 3 Weight	256.00 lb(US) (116.12 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information