HMIG3UFC

Base unit, Harmony GTU, Premium BOX for Universal Panel





Main

TTT CALL	
Range of Product	Harmony GTU
Product or Component Type	Base unit
Device short name	Premium Box
Range Compatibility	Harmony GTU
[Us] rated supply voltage	1224 V DC power supply

Complementary

Complementary	
Integrated connection type	Ethernet TCP/IP 2 RJ45 COM1 serial link RJ45 RS485 110115200 bit/s COM1 serial link RJ45 RS485 187.5 kbit/s COM2 serial link SUB-D 9 RS232C/RS422/RS485 110115200 bit/s COM2 serial link SUB-D 9 RS232C/RS422/RS485 187.5 kbit/s COM2 serial link SUB-D 9 RS232C/RS422/RS485 187.5 kbit/s Auxiliary port terminal block Expansion unit fieldbus card USB 2.0 port 2 USB type A USB 2.0 port mini B USB
Communication port protocol	Modbus Uni-Telway Modbus TCP/IP
Operating system	Harmony
Software package	Vijeo Designer run time
Processor name	CPU RISC 600 MHz
Data storage equipment	1 GB SD card
Port Ethernet	10BASE-T/100BASE-TX/1000BASE-T
Memory description	256 MB RAM internal 512 KB NVRAM backup memory
Type of cooling	Natural convection
Width	7.40 in (188 mm)
Height	5.16 in (131 mm)
Depth	1.77 in (45 mm)
Net Weight	1.98 lb(US) (0.9 kg)

Environment

Standards	CSA C22.2 No 142
Standards	
	ANSI/ISA 12-12-01 UL 508
	UL 508
	Class I division 2 CSA C22.2 No 213
	IEC 61132-2
Product certifications	CE[RETURN]CULus[RETURN]ATEX[RETURN]IEC-
	Ex[RETURN]RCM[RETURN]GL[RETURN]KC[RETURN]CUL[RETURN]EAC[RETUR
Ambient air temperature for operation	32140 °F (060 °C)
Ambient air temperature for storage	-4140 °F (-2060 °C)
Pollution degree	2 EN 61131-2 Ed.3
Relative Humidity	1090 % non-condensing
Operating altitude	6561.68 ft (2000 m)

Vibration resistance	3.5 mm constant amplitude 59 Hz) EN/IEC 61131-2 9.8 m/s² 9150 Hz) EN/IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to EN/IEC 61000-4-2

Ordering and shipping details

Category	22567-MAGELIS HMI GTU
Discount Schedule	MC2
GTIN	3606480841620
Returnability	No
Country of origin	SG

Packing Units

PCE
1
5.31 in (13.5 cm)
8.27 in (21.0 cm)
10.24 in (26.0 cm)
2.41 lb(US) (1.091 kg)
S04
4
11.81 in (30.0 cm)
15.75 in (40.0 cm)
23.62 in (60.0 cm)
10.90 lb(US) (4.944 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.


Product data sheet Dimensions Drawings

HMIG3UFC

Dimensions

External Dimensions

in. (3)



- 1 Front
- 2 Left
- 3 Bottom