

**K155H-42-MED**

K155H-42-MED 4.25" PAR16/PAR20 DEEP REMODEL HOUSING - IC / NON-IC



NAME:

TYPE:

DATE:

NOTES:

**SPECIFICATIONS**

VOLTAGE: 120V

**HOUSING DETAILS:** These housings are constructed of heavy-duty steel and a tight assembly so as to avoid noise and vibration.

For use with a PAR20 or MRE26 (PAR16) style bulb, in either a halogen or LED type.

Insulated Ceiling Application; the use of an LED type bulb is required. Refer to trim model for specific bulb wattages.

The mounting system allows a quick, easy and sturdy installation, using the automatic positioning feature (i.e., has a 2 screw system).

Approved for damp locations, with built-in thermal protection and "Quick Connect wire connectors included.

Some municipalities will require the use of a vapor barrier in an insulated application. Verify local building codes prior to installation.

**COMPATIBLE TRIMS:** TR1325 - 4.25" PAR20 SHOWER TRIM  
TR1350 - 4.25" PAR20 GIMBAL TRIM  
TR1510 - 4.25" PAR16 REGRESSED TRIM  
TR1530 - 4.25" PAR16 GIMBAL TRIM

CUTTING HOLE: 4.38" (111.3mm)

MOUNTING PLATE: MP425 / AMP425 / MPH425

WARRANTY: 1 year

HEIGHT: 5.75" (146.1mm)

LENGTH: 10.29" (261.4mm)


**APPLICATIONS**

Can be installed in ceilings with, up to 1.25" (32mm) of thickness, New Construction or acoustic tiles.

# K155H-42-MED

K155H-42-MED 4.25" PAR16/PAR20 DEEP REMODEL HOUSING - IC / NON-IC

## DIMENSIONS



## ACCESSORIES



### INSULATED BOX

The ib410 insulated box is built for ceilings with insulation. to be used in conjunction with any ndr remodel housings.

## RATINGS



## ORDERING GUIDE

### K155-MED SERIES

Series	Product
K155H-42-MED	4.25" Deep Remodel Housing-PAR20 / PAR16
Notes:	Configure product using <b>BOLD</b> options: Ex: <b>K155H-42-MED</b>