

8501XDO80XDLV53

NEMA Control Relay, Type X, latching, 10A
resistive at 600 VAC, 8 normally open contacts,
24 VDC coil



Principal

Range	8501X
Relay Type	Accrochage
Product	Relais
Current Rating	10 A AC 5 A DC
Contact Configuration	8F 8 standard contact cartridges
Number of Poles	8P
Coil Voltage	24 V DC
Voltage Rating	250 V DC
Mounting Type	Panneau
Operating Temperature	-40...71 °C
Electrical Connection	Borniers à vis-étrier
Certifications	CE CSA Listé UL
Operating Time	37 ms - déclenchement 45 ms - perte de niveau

Emballage

Poids de l'emballage (Kg)	1,692 kg
---------------------------	----------

Offre de la durabilité

Statut environnemental de l'offre	Produit Green Premium
Régulation REACH	Déclaration REACH
Directive RoHS UE	Conformité pro-active (Produit en dehors du scope légal RoHS UE) Déclaration RoHS UE

Sans mercure	Oui
Information sur les exemptions RoHS	Oui
Régulation RoHS Chine	Déclaration RoHS pour la Chine
Profil environnemental	Profil environnemental du Produit
Profil de circularité	Informations de fin de vie

Garantie contractuelle

Garantie	18 months
----------	-----------