

ORDERING INFORMATION


Order code: 51174
 Description: F32T8/FS/RS/G13/STD
 UPC: 69549011748
 Case quantity: 25




PERFORMANCE DATA

Shape: T8
 Base: G13 (Med Bipin)
 Starting method: Rapid Start (RS)
 Wattage (W): 32
 Colour temperature (K): 5 700
 CRI: 92
 Rated life on IS¹ ballast:
 Based on a 3 hour start 20 000
 Based on a 12 hour start 24 000
 Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 24 000
 Based on a 12 hour start 30 000
 Initial lumens (lm): 2 300
 Mean lumens (lm): 2 185
 Nominal efficiency (lm/W): 72
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T8 800 series ballast.



E Means this bulb meets federal minimum efficiency standards.