

Technical Information Bulletin Fluorescent

E-Lume™

ORDERING INFORMATION

Order code: 56516
Description: FC8T9/CW/RS/4P/ELUME
UPC: 69549565166
Case quantity: 24




Nominal diameter : 9 in. (229 mm) Dia. : 1 5/32 in. (29.5 mm)

PERFORMANCE DATA


Shape: T9
Base: 4 pin
Starting method: Rapid Start (RS)
Wattage (W): 22
Colour temperature (K): 4 100
CRI: 60
Rated life on IS¹ ballast:
Based on a 3 hour start 6 000
Initial lumens (lm): 1 150
Mean lumens (lm): 1 095
Nominal efficiency (lm/W): 52
TCLP compliant: Yes
Phosphor composition: Triphosphor
Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



A Max	B Min / Max	C Max
Inner diameter from base to tube	Inner diameter from tube to tube	Outer overall diameter from base to tube
6.06 in. 154.0 mm	5.82 in. / 11.91 in. 148.0 mm / 153.0 mm	8.28 in. / 210.5 mm

SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T9 Circline ballast.

