

Kellems Wire Management,
Liquidtight System, Straight, 3/4",
Non-Insulated with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [074093403](#)

Kellems Wire Management, Liquidtight System, Straight, 3/4",
Non-Insulated with Mesh

Application

- 3/4" NPT

Performance

- Environmental - Flammability - UL 94-HB and UL 94-V2
- Environmental - Hazardous Location - Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2
- Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

General

Catalog Number	074093403
Material	Steel Fitting, Stainless Steel Mesh
Series	Liquidtight Conduit
Style	For Metal & Non-Metallic PolyTuff I



Type	Straight With Male Fitting
UPC	783585331621

Dimensions

Conduit Trade Size	3/4 in
--------------------	--------

Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalogs - WDK Catalog Full 2024](#)
- [Literature - Wire Management Solutions Brochure](#)
- [Specifications - 74093403](#)
- [Warranty - Industrial & Commercial Products](#)