

Representative

Catalog Number:12JMLC72/2LGProduct ID:7TBA127590R1551UPC Number:78268341207

Status: Active

Battery Unit, Battery Type: lead-calcium, Voltage DC: 12V, Battery Wattage: 72W, Colour: factory white, 120VAC, self-powered, Lamp Type: MR16 LED, two lamps, Lamp Voltage: 12V, Lamp Wattage: 4W, Head Style: standard, line cord, Battery Run Time (Minimum): 30 minutes

Fully-automatic labour-saving commercial emergency lighting unit. The JMLC Series battery unit incorporates a complete range of high performance and laboursaving features normally found only in higher voltage units. The JMLC Series battery unit is ideally suited for any commercial application where space and ease of installation are considerations.

- Quick and easy installation pre-assembled cordset, no batteries or board to remove before installation
- Universal Spider knockout pattern for junction box mounting
- Fully automatic solid-state charger with test switch and AC-on pilot light
- · Sealed dust-proof transfer relay circuit and low-voltage disconnect
- · Long-life, maintenance-free sealed lead battery
- · NEXUS compatible

North American Specifica	ations (UNSPSC)
UNSPSC	39111709 Emergency light unit
IGCC	3940 Emergency light unit
Brand Name	Emergi-Lite
Туре	Battery Unit
Application	Institutional, Commercial, Hospitality
Standard	CSA
Wattage	72W
Voltage Rating	120VAC, 12VDC
Battery	Lead-calcium
Battery Runtime	30 minutes
Lamp Type	MR16 LED
Number Of Lamps	2
Size	9-1/8 Inches Height x 12-3/4 Inches Width
Material	Steel
Mounting	Wall
Color	Factory White
Lamp Wattage	4W
Packaging	

Packaging	
Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	10 lbs. Each

Documents / Support Tools	
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support http://www.tnb.ca/en/contactus/?id=ALL Hours: 7h00 - 18h00 Monday-Friday



www.tnb.ca