

YGHR26C34TN Figure 8 **Compression Ground Rod** Connector

By Burndy Catalog # YGHR26C34TN

HYTAIL™ Ground Rod Figure 8 Compression Tap Connector.

Features

- High torque strength ground rod connector accepts a wide range of copper conductors to ground rod
- UL467 Listed
- · Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

General

Catalog Number YGHR26C34TN Connector Type Tap Die Index 998;1012 Material Copper Physical Attribute - Number of Crimps Required

Plated

Plating Type Tin - Electro Plated

HYTAIL™ Trade Name Type Taps

UPC 781810255193 UPC 12 Digit 7818102551933

Dimensions

Dimension - B Length fraction 22/25 in Dimension - B Length inch 0.88 in Dimension - Ground Rod Size 3/4 Dimension - Height fraction 2-15/79 in Dimension - Height inch 2.19 in Dimension - Height mm 55.6 mm Dimension - L Length Overall 22 mm

Dimension - Length Overall 0.88 in

inch

Conductor Related

Conductor - Copper Str Size 2 AWG;1 AWG;1/0 ;2/0 AWG



Conductor - Copper Str Size 2 AWG - 2/0 AWG

Range

Conductor - Rod Size 3/4 in Conductor - Rod Size Range 3/4 in

 CU C Str-Size A Conductor Type

Rod-Size B

Certifications And Compliance

Certification - CSA Approved Yes Certification - ETL Certification - UL Listed Direct Yes Burial

Certification - UL Recognized Nο Certification - cULus Nο

Industry Standard(s) UL467 IFFF 837

Standards - Industry Standards UL467;IEEE 837

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

Carton Quantity 20 Minimum Pack Quantity Pallet Quantity 4640

Product Assets

3D Models - YGHR26C34TN MODEL-PDF 3D Models - YGHR26C34TN MODEL-STEP

3D Models - YGHR26C34TN MODEL-IGES

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - sd..088266-01 Specifications - YGHR26C34TN

