

**H6,0/15****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)For conductors from 0.25 to 6,0 mm<sup>2</sup> (AWG 24 - 10)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in polybag

**General ordering data**

|            |                                              |
|------------|----------------------------------------------|
| Version    | Wire-end ferrule, Standard, 15 mm, 15 mm, No |
| Order No.  | <a href="#">0124700000</a>                   |
| Type       | H6,0/15                                      |
| GTIN (EAN) | 4008190003807                                |
| Qty.       | 500 pièce(s)                                 |
| Packaging  | loose                                        |

H6,0/15

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0,302 g |
|------------|---------|

## Technical data

|                        |                                         |         |          |
|------------------------|-----------------------------------------|---------|----------|
| Description of article | Wire end ferrule without plastic collar | Version | Standard |
|------------------------|-----------------------------------------|---------|----------|

## Wire-end ferrules

|                                         |        |                             |                   |
|-----------------------------------------|--------|-----------------------------|-------------------|
| Collar diameter (D2)                    | 4,7 mm | Conductor cross-section     | 6 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 3,5 mm | Contact surface length (L2) | 15 mm             |
| L1 in mm                                | 15 mm  | Stripping length            | 15 mm             |
| Wire connection cross section AWG, max. | AWG 10 |                             |                   |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |
| ECLASS 14.0 | 27-40-02-01 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E499744    |

## Downloads

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

**H6,0/15**

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Dessins

