

ZCE62

limit switch head ZCE - side metal plunger
adjustable



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKT XCKD XCKP
Associated body	ZCT28G11 ZCD29M12 ZCP37 ZCD21 ZCMD81L2 ZCT26P16 ZCMD69C12 ZCMD21M12 ZCMD21L08U78 ZCMD81L5 ZCD26 ZCP25 ZCMD61C12 ZCP35 ZCP29M12 ZCD25 ZCT28N12 ZCMD37L5 ZCT21P16 ZCT28P16 ZCMD39L5 ZCT25N12 ZCMD41L2 ZCMD21L08R12 ZCT27N12 ZCP21

ZCP29
 ZCMD25L5
 ZCP26
 ZCMD21L1
 ZCT25G11
 ZCD39
 ZCMD39L1
 ZCMD21C12
 ZCT21N12
 ZCD27
 ZCMD29L1
 ZCMD21L5
 ZCMD37L2
 ZCD28
 ZCMD41L5
 ZCMD41L1
 ZCT21G11
 ZCMD25L2
 ZCMD37L1
 ZCMD81L1
 ZCT26N12
 ZCD29
 ZCP39
 ZCD31
 ZCT27P16
 ZCMD25L1
 ZCD21M12
 ZCT26G11
 ZCP21M12
 ZCD37
 ZCP27
 ZCP28
 ZCMD21L2
 ZCD35
 ZCP31
 ZCMD29L5
 ZCMD61M12
 ZCT27G11
 ZCMD29L2
 ZCT25P16
 ZCMD39L2
 ZCMD29C12

Movement of operating head	Linear
Type of operator	Side plunger spring return metal adjustable)
Type of approach	Vertical approach, 1 direction

Complementary

Positive opening	With
------------------	------

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.12 lb(US) (0.055 kg)
Package 1 Height	0.180 dm
Package 1 width	0.500 dm
Package 1 Length	0.320 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------