

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure Stainless steel – WM 8018.474

Date : Feb 4, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure Stainless steel – WM 8018.474 - WM242412N4

: 04.02.2019 build on www.rittal.com/ca-en



Product description	
Material:	Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated
Surface finish:	Brushed
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Housing with door(s) Door hinged on left Mounting plate Wall mounting blind-nuts
Product features	
Dimensions:	Height: 600 mm (24 ") Width: 600 mm (24 ") Depth: 300 mm (12 ")
Material thickness::	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ") Mounting plate: 2.5 mm (0.1 ")
Mounting plate:	Height: 570 mm (22 ") Width: 549 mm (22 ")
Lock version:	Quarter turn

Packaging unit:	1 pc(s).
Weight/packaging unit:	28 kg (61.7 lb.)
EAN:	83496
Approvals	
Approvals:	UL + C-UL