



Zinc Mate<sup>™</sup>, 368 Grams No. 73054 | Item# 1006158 | Case# 1006157

Product Description High Performance coating of >93% pure zinc that

electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly.

Applications On threads, exposed edges, fasteners, conduit, strapping,

welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails. Meets ASTM A780

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC

Generic Description 1 Instant Cold Galvanized Coating

Net Fill 368 Grams

UPC Code 078254730547

Unit Dimensions 23.5H x 6.68W x 6.68D cm

Units Per Case 12

Case Dimensions 25.88H x 21.43W x 28.72D cm

Cases Per Pallet 90

Case Weight 7.71 kg

I 2 of 5 Code 30078254730548

Appearance Gray Viscous Liquid

Flash point (F) -19°C
Flash point (C) -28°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.77 to 0.85

Plastic Safe Yes

Evaporation Rate Fast

Dry Time - Fully Dry 8 Hours

Dry Time - Tack Free 20 Minutes

Recoat Before 1 Hour or After 48 Hours
Coverage 2.6 to 3.0 Sq M at 3 Mils Dry

Last revised: 2/12/2020

Page 1 of 2







Working Temp (F) 130°F (Continuous) / 150°F (Intermittent)
Working Temp (C) 54.4°C (Continuous) / 65.6°C (Intermittent)

Propellant Hydrocarbon

Aerosol Flammability Level

Military Specification

Number

**DOT Proper Shipping Name** 

Restricted from Sale In:

Removal (How To)

1

Meets requirements of Mil-P-26915, Meets requirements of

Mil-P-46105

Not for sale in United States.

Remove with aromatic solvents, Xylene. Toluene can be

used, but is not recommended.

Aerosols, Flammable, Limited Quantity

Last revised: 2/12/2020

Page 2 of 2

