



### Main

Range of product	Homeline
Product or component type	Load Center
Line Rated Current	100 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	22 kA

### Complementary

Electrical connection	Lugs
AWG gauge	AWG 6...AWG 2/0 aluminium/copper
Load center type	Main breaker
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover colour	White
Box number	10

### Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 (indoor)
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>