



Main

| | |
|-----------------------------|--------------------------|
| Range of Product | Harmony 9001BW |
| Product or Component Type | Complete control station |
| Device short name | 9001BW |
| Control station application | Two functions |
| Colour of base of enclosure | Grey |

Complementary

| | |
|--------------------------------|---|
| Material | Cast aluminium |
| Cable entry | 1 entry for 1/2" - 14 NPT |
| CAD overall width | 2.76 in (70 mm) |
| CAD overall height | 4.25 in (108 mm) |
| CAD overall depth | 3.58 in (91 mm) |
| Type of operator | maintained |
| Control station composition | 1 flush push-button, black, white ON 1 flush push-button, black, white OFF |
| Contacts type and composition | 1 NO + 1 NC |
| Contact operation | Interlocked |
| Mechanical durability | 5000000 cycles |
| [Ie] rated operational current | 0.6 A 600 V, AC-1/DC-1 0.75 A 480 V, AC 1.5 A 240 V, AC 3.75 A 120 V, AC |
| Device mounting | Surface |
| Type of Installation | Indoor/outdoor |

Environment

| | |
|---------------------------------------|---|
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| NEMA degree of protection | NEMA 1 NEMA 4 |
| Standards | UL 508 EN/IEC 60947-5-5 EN/IEC 60947-1 CSA C22.2 No 14 EN/IEC 60947-5-4 JIS C 4520 EN/IEC 60947-5-1 |
| Product Certifications | UL Listed[RETURN]CSA |
| Environmental characteristic | Waterproof Dustproof |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-------------------|--------------------------------|
| Category | 21421-9001 B (NOT BW70 - BW80) |
| Discount Schedule | CS1 |
| GTIN | 785901857747 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.89 in (22.581 cm) |
| Package 1 Width | 3.50 in (8.89 cm) |
| Package 1 Length | 22.58 in (57.355 cm) |
| Package 1 Weight | 2.50 lb(US) (1.134 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|