



Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 2, 3 pole, 3 phase, 45A, 600VAC

9065SEO8

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	S
Product destination	Starter
Thermal overload type	Melting alloy

Complementary

NEMA size	2
Phase	3 phase
Number of thermal units required	3
Mounting Support	Panel
Product or Component Type	Overload relay
[Ue] rated operational voltage	600 V AC
Height	3.3 in (84.1 mm)
Width	3.5 in (88.9 mm)
Depth	4.0 in (100.8 mm)

Ordering and shipping details

Category	US10CP121661
Discount Schedule	0CP1
GTIN	785901893707
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.70 in (11.938 cm)
Package 1 Width	5.20 in (13.208 cm)
Package 1 Length	5.30 in (13.462 cm)
Package 1 Weight	17.600 oz (498.952 g)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

Use Again

○ Repack and remanufacture	
Take-back	No