

Product data sheet

Characteristics

SSP04XDSE15A1

Surge protection device, XDSE, 150kA,
480Y/277 VAC, 3 phase, 4 wire, SPD type 1



Main

Product

Surge protection device

Complementary

Voltage Rating	480Y/277 V AC
MCOV	320 V
Surge Current	150 A per phase
Voltage Protection Rating	1200 V L-N 1200 V L - G 1200 V L - L 2000 V N - G
Rated Current	20 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

Environment

Enclosure Rating	NEMA 4X
------------------	---------

Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	3606486149287
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.70 in (14.48 cm)
Package 1 Width	10.90 in (27.69 cm)
Package 1 Length	13.20 in (33.53 cm)
Package 1 Weight	4.37 lb(US) (1.982 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes