Product data sheet
Characteristics

NSYMR128
Monobloc perforated plates H1200xW800mm with universal perforations 11x26mm

Green Premium Product

Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 47.24 in (1200 mm) W: 31.50 in (800 mm)
Mounting Location	Direct fixing on backstuds Step slide
Mounting plate description	Telequick perforated
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM
Quantity per Set	Set of 1
Material	steel
Surface Finish	Zinc coated

Complementary

Fixing mode	Screwed on backstuds M8 By fixing element
Height	45.08 in (1145 mm)
Width	29.57 in (751 mm)
Depth	0.59 in (15 mm)
Thickness	0.08 in (2 mm)
Net Weight	14.11 lb(US) (6.4 kg)
Number of slots	1800
Variant particularity	Installation in rear of enclosure
Cut-out dimensions	11 x 26 mm

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480183591
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.59 in (1.5 cm)
Package 1 Width	29.53 in (75.0 cm)
Package 1 Length	45.08 in (114.5 cm)
Package 1 Weight	13.36 lb(US) (6.062 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	63

Package 2 Height	35.04 in (89.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	870.83 lb(US) (395.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric