

# QO1515

## 15-15A 1P QO TANDEM BREAKER

### Main

Ampere Rating	15A/15A
Approvals	UL Listed - CSA Certified
Circuit Breaker Type	Replacement Tandem
Depth	2.91 Inches
Features	VISI-TRIP trip indication
For Use With	Old style non-class CTL Load Centers (Replacement Only)
General Application	Provides overload and short circuit protection
HACR Rated	Yes
Height	3.00 Inches
Marketing Trade Name	QO
Mounting Type	Plug-On
Number of Poles	1-Pole
Phase	1-Phase
Short Circuit Current Rating	10kA
Space Required	1
Terminal Type	Pressure Plate
Type	QO
Voltage Rating	120/240VAC
Width	0.75 Inches
Wire Size	#14 to #8 AWG(Al/Cu)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.