



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKT XCKP XCKD
Associated body	ZCMD21C12 ZCMD21L08U78 ZCMD25L5 ZCT21G11 ZCMD41L1 ZCT27P16 ZCD29M12 ZCD21 ZCP37 ZCMD41L2 ZCD25 ZCMD21L5 ZCMD39L1 ZCP27 ZCP35 ZCP28 ZCT28G11 ZCT26N12 ZCD39 ZCT25G11 ZCMD39L5 ZCT21P16 ZCP25 ZCMD81L1 ZCD31 ZCT28P16

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD81L5
 ZCMD69C12
 ZCT27N12
 ZCD21M12
 ZCT25N12
 ZCD26
 ZCP21M12
 ZCP39
 ZCMD25L1
 ZCT25P16
 ZCT21N12
 ZCP29
 ZCMD37L2
 ZCMD61C12
 ZCD28
 ZCD37
 ZCT26G11
 ZCP21
 ZCMD81L2
 ZCMD37L1
 ZCMD25L2
 ZCP29M12
 ZCMD29L1
 ZCMD37L5
 ZCMD41L5
 ZCMD21M12
 ZCT28N12
 ZCT26P16
 ZCMD21L08R12
 ZCMD21L1
 ZCP26
 ZCD27
 ZCMD29L2
 ZCT27G11
 ZCMD39L2
 ZCMD61M12
 ZCP31
 ZCD35
 ZCMD21L2
 ZCMD29C12
 ZCMD29L5
 ZCD29

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral or vertical approach, 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.06 lb(US) (0.026 kg)
Package 1 Height	0.160 dm
Package 1 width	0.500 dm
Package 1 Length	0.300 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------